

70s Trans-am/Group 5

Schedule

Date	Location	Track
11/30/2025	SpeedZone	Moody Mile
12/14/2025	The Race Place	Cyclone
1/11/2026	SpeedZone	Moody Mile
1/25/2026	Dom's	King Cobra
2/22/2026	The Race Place	Hurricane

General Rules and Race Day Procedures

3-minute heats, 2 minutes in between. European rotation

45 - second qualifying, Qualifying will be done by laps and sections.

Cars will be impounded from tech till end of race. No changes to cars will be allowed after tech. If a tire or wheel is badly damaged, you will be allowed to change that one tire. All repairs will be made with the track on or in between heats. If there is a sit out the sit out car will go to impound and may not be worked on. If there are multiple mains cars will go back to impound till all races are finished

Be the best racer by marshaling, without marshals we can't race. Unsportsmanlike conduct will not be tolerated. Unsportsmanlike conduct (at the race directors' discretion) will result in a 5-lap penalty.

Raceways will open at 11:30, and the track will be on for practice at 12:00

Tech will open from 1:00 till 1:15, qualifying will follow. After the first race the track will be on for 30 minutes for the next class and tech will follow that practice session. The only cars on the track should be cars for the class to race next.

Pit pass will be \$15; each class will be \$10.

Points

1 st - 50 points	6 th - 45 points	11 th - 40 points	16 th - 35 points	21 st - 30 points
2 nd - 49 points	7 th - 44 points	12 th - 39 points	17 th - 34 points	22 nd - 29 points
3 rd - 48 points	8 th - 43 points	13 th - 38 points	18 th - 33 points	23 rd - 28 points
4 th - 47 points	9 th - 42 points	14 th - 37 points	19 th - 32 points	24 th - 27 points
5 th - 46 points	10 th - 41 points	15 th - 36 points	20 th - 31 points	25 th - 26 points

26th on will receive 25 points.

1 additional point will be awarded for:

Top Qualifier, fastest in race lap per class, and Main winners

If it's not stated, it's not legal!

70s Trans-am

Chassis: JK cheetah 21 D or C can, JK25, JKC43 Aeolos, Parma Flexi 5, Champion Turbo Flex, ProSlot SpeedFX C or D. No aluminum pans or chassis. You must use the chassis as they are manufactured with no interchanging parts or pans, you must use stock motor brackets. The only modifications are Pin tubing, tape and lead may be added

Motor: JK Hawk 7 Motor JKM7 – JKP30307 motor, NO BALL BEARINGS, if a motor is deemed open or altered the motor will be impounded from the racer.

Body: JK Mustang 1971 .010 B124B/JK7254B, JK Camaro 1971 .010 B123B/JK7253B, JK AMC Javelin .010 B138B/JKP7355B

Must be painted and have a 3-color, 3D interior, mustang may add ¼ inch lexan or tape spoiler to the back of body only.

Gears: 64 or 48 pitch gears only. No metal spur gears.

Axles: 3/32 or 1/8 any axle, no hollow axles, no ball bearings, oilites only.

Tires: Any black foam or black rubber, no speed rubber. Must use front wheel stickers or 1/2 inch or larger front wheels

Misc: Any non-weighted guide flag, any flag nut, any lead wire. May add wire hold down (earring back) to Champion Turbo Flex, Flexi 5, and ProSlot SpeedFX. Any copper braid, no silver or coated braid. Body bullet proofing will be allowed by lexan or tape.

Tech: .032 clearance for chassis, gear, and motor. 83mm rear tire width. Body's cut on the cutline. Must have at least a 1¼-inch front splitter. All motors will be measured for squeezing and shortening before or after the race.

Group 5

Chassis: JK Cheetah 21 D or C can, JK25, JKC43 Aeolus, Parma Flexi 5, Champion Turbo Flex, Mossetti 1234 or Mossetti Patriot Striker (2-piece chassis Part # MR-1002), ProSlot SpeedFX C or D can. No aluminum pans or chassis. You must use the chassis as they are manufactured, with no interchanging parts or pans, and you must use stock motor brackets. The only modifications are, Pin tubing, tape and or lead may be added

Motor: JK Hawk 9 JKM9/M9 motor, NO BALL BEARINGS, if a motor is deemed open or altered the motor will be impounded from the racer.

Body: JK Porsche 908 JKB144B/JK7503B .010, JK Ferrari 312 JKB57B/JK7089B .010, JK Lola 280 JKB142B/JK7501B .010
Must be painted and have a 3-color interior

Gears: Spec 11 tooth pinion, any 64 or 48 pitch plastic spurs only

Axles: 3/32 or 1/8 any axle, no hollow axles, no ball bearings, oilites only.

Tires: any black foam or black rubber no speed rubber. Must use front wheel stickers or 1/2 inch or larger front wheels

Misc: Any non-weight guide flag. Any flag nut. Any lead wire. May add wire hold down (earring back) to Champion, SpeedFX or Flexi 5. Any braid. Body bullet proofing will be allowed by lexan or tape.

Tech: .032 clearance for chassis, gear, and motor. 83mm rear tire width. Body's cut on the outline. Must have at least a 1\4-inch front splitter. All motors will be measured for squeezing and shortening before or after the race